Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: FOSTER 60-90
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Masking material
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Temati Rijnland 2

NL-1948 RL Beverwijk Tel: +31 251 229 172 E-mail: temati@temati.com

- · Further information obtainable from: Regulatory Department
- · 1.4 Emergency telephone number: +44 (0) 1235 239 670 (24 hrs)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

Lact. H362 May cause harm to breast-fed children.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS09

GHS02

GHS07

· Signal word Warning

· Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom.

alkanes, C14-17, chloro

Xylene, mixed isomers, pure

· Hazard statements

H226 Flammable liquid and vapour.

May cause harm to breast-fed children.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

(Contd. of page 1) Toxic to aquatic life with long lasting effects.

H411

· Precautionary statements

P243 Take action to prevent static discharges.

P263 Avoid contact during pregnancy and while nursing.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

Store in a well-ventilated place. Keep container tightly closed. P403+P233

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · **Description:** Mixture of substances listed below with additions.

Dangerous components:		
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. The property of the property of the state of the property of the state of the property of the state of the	25-<50%
CAS: 85535-85-9 EINECS: 287-477-0 Reg.nr.: 01-2119519269-33	alkanes, C14-17, chloro Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	5-<10%
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32	Xylene, mixed isomers, pure → Flam. Liq. 3, H226; → STOT RE 2, H373; Asp. Tox. 1, H304; → Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	1-<3%
CAS: 1309-64-4 EINECS: 215-175-0 Reg.nr.: 01-2119475613-35	Antimony trioxide © Carc. 2, H351	<1%
CAS: 61789-77-3 EINECS: 263-087-6 Reg.nr.: 01-2119486994-16	Quaternary ammonium compounds, dicocoalkyldimethyl, chlorides Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 2, H411; Acute Tox. 4, H302	<1%
CAS: 41556-26-7 EINECS: 255-437-1	Bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Sens. 1, H317	<1%

[·] Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air or oxygen; call for doctor.
- · After skin contact:

Immediately rinse with water.

If skin irritation continues, consult a doctor.

(Contd. on page 3)

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

(Contd. of page 2)

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

Sand. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents:

Water

Water with full jet

· 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Use only in well ventilated areas.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.

(Contd. on page 4)

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

(Contd. of page 3)

11 mg/kg bw/day (General Population)

65.3 mg/m3 (General Population)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· DNELs

- · Additional information about design of technical facilities: No further data; see item 7.
- · Ingredients with limit values that require monitoring at the workplace:

CAS: 1330-20-7 Xylene, mixed isomers, pure

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV

· Regulatory information WEL: EH40/2020

CAS: 6474	12-95-6 Solvent naphtha (petroleum), light arom.
Oral	Long-term - systemic effects, general population

Long-term - systemic effects, worker 25 mg/kg bw/day (Worker) Dermal Long-term - systemic effects, general population 11 mg/kg bw/day (General population) Inhalative Long-term - systemic effects, worker 150 mg/m3 (Worker) Long-term - systemic effects, general population 32 mg/m3 (General Population)

CAS: 85535-85-9 alkanes, C14-17, chloro

Oral Long-term - systemic effects, general population 0.58 mg/kg bw/day (General Population) Dermal Long-term - systemic effects, worker 47.9 mg/kg bw/day (Worker) Long-term - systemic effects, general population 28.75 mg/kg bw/day (General population) Inhalative Long-term - systemic effects, worker 6.7 mg/m3 (Worker) Long-term - systemic effects, general population 2 mg/m3 (General Population)

CAS: 1330-20-7 Xylene, mixed isomers, pure

Long-term - systemic effects, general population 12.5 mg/kg bw/day (General Population) Oral Dermal Long-term - systemic effects, worker 212 mg/kg bw/day (Worker) Long-term - systemic effects, general population 125 mg/kg bw/day (General population) Inhalative Acute - Local effects, worker 442 mg/m3 (Worker) Long-term - systemic effects, worker 221 mg/m3 (Worker) Long-term - local effects, worker 221 mg/m3 (Worker) Acute - systemic effects, general population 260 mg/m3 (General Population) Acute - systemic effects, worker 442 mg/m3 (Worker) Acute - local effects, general population 260 mg/m3 (General Population) Long-term - systemic effects, general population 65.3 mg/m3 (General Population)

· PNECs

CAS: 85535-85-9 alkanes, C14-17, chloro

Aquatic compartment - sediment in freshwater 5 mg/kg sed dw Aquatic compartment - sediment in marine water 1 mg/kg sed dw 10.5 mg/kg dw Terrestrial compartment - soil Sewage treatment plant 80 mg/L

Long-term - local effects, general population

CAS: 1330-20-7 Xylene, mixed isomers, pure

Aquatic compartment - freshwater 0.327 mg/L (not specified)

(Contd. on page 5)

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

Aquatic compartment - marine water

Aquatic compartment - sediment in freshwater

Aquatic compartment - sediment in marine water

Aquatic compartment - sediment in marine water

12.46 mg/kg sed dw (not specified)

Terrestrial compartment - soil

2.31 mg/kg dw (not specified)

Sewage treatment plant

(Contd. of page 4)

12.46 mg/kg sed dw (not specified)

5.58 mg/L (not specified)

· Ingredients with biological limit values:

CAS: 1330-20-7 Xylene, mixed isomers, pure

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- Regulatory information BMGV: EH40/2011
- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Respiratory protection:



Filter A

· Protection of hands:

Not required.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material: ≥ 0.12 mm

· Penetration time of glove material

> 480 min.

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Use protective suit.

- G

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

(Contd. of page 5)

SECTION 9: Physical and chemic	ical properties
9.1 Information on basic physical and c	chemical properties
General Information	memous properties
Appearance:	
Form:	Pasty
Colour:	White
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Neutral
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	2: 165-181 °C
Flash point:	50 °C (DIN 53213)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	>400 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive as
• • •	vapour mixtures are possible.
Explosion limits:	
Lower:	1 Vol %
Upper:	7 Vol %
Vapour pressure At 20 °C:	<10 hPa
Vapour pressure At 50 °C:	13 hPa
Density At 20 °C:	1.2 g/cm³ (DIN 51757)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic At 20 °C:	880,000 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	43.9 %
Water:	0.1 %
Solids content:	55.0 % (DIN 53216)
9.2 Other information	
VOC (EU):	43.92 %
VOC (EÚ):	527.1 g/l
VOCV:	43.92 %

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

(Contd. on page 7)

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

(Contd. of page 6)

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: Carbon monoxide

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	· LD/LC50 values relevant for classification:		
CAS: 6474	CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	3,492 mg/kg (RAT)	
Dermal	LD50	>3,160 mg/kg (RABBIT)	
Inhalative	LC50/4 h	>6,193 mg/l (RAT)	
CAS: 8553	CAS: 85535-85-9 alkanes, C14-17, chloro		
Oral	LD50	>2,000 mg/kg (RAT)	
	LC50/96 h	>5,000 mg/l (Fish)	
CAS: 1330	CAS: 1330-20-7 Xylene, mixed isomers, pure		
Oral	LD50	3,523-4,000 mg/kg (RAT)	
Dermal	LD50	12,126 mg/kg (RABBIT)	
Inhalative	LC50/4 h	6,350 mg/l (RAT)	
CAS: 1309-64-4 Antimony trioxide			
Oral	LD50	3,250 mg/kg (rat)	

- Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Additional toxicological information: No further relevant information available.
- · Ingestion:
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity

May cause harm to breast-fed children.

- · STOT-single exposure
- May cause respiratory irritation. May cause drowsiness or dizziness.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.

LL50/96 h | 9.2 mg/l (SALMO GAIRDNERI / ONCORHYNCHUS MYKISS)

EL50/48 h 3.2 mg/l (DAPHNIA MAGNA)

CAS: 85535-85-9 alkanes, C14-17, chloro

EC50/48 h 0.006 mg/l (DAPHNIA MAGNA)

EC50/96 h >3.2 mg/L (SELENASTRUM CAPRICORNUTUM)

- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 8)

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

(Contd. of page 7)

- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Dispose of as dangerous waste.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

CHOMICAL	14: Transport	• •
	4. Iranchart	INTOVMATION
	T. II WIISPUIL	III OI III UII OII
		and the second s

· 14.1 UN-Number · ADR/RID/ADN, IMDG, IATA	UN1139
· 14.2 UN proper shipping name	
· ADR/RID/ADN	1139 COATING SOLUTION, ENVIRONMENTALLY
	HAZARDOUS
· IMDG	COATING SOLUTION (Solvent naphtha (petroleum), light
	arom., alkanes, C14-17, chloro), MARINE POLLUTANT
· IATA	COATING SOLUTION

- · 14.3 Transport hazard class(es)
- · ADR/RID/ADN, IMDG



· Class 3 Flammable liquids.

· Label

 \cdot IATA



· Class 3 Flammable liquids.

· Label

(Contd. on page 9)

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

	(Contd. of page
14.4 Packing group ADR/RID/ADN, IMDG, IATA	III
14.5 Environmental hazards:	Product contains environmentally hazardous substances alkanes, C14-17, chloro
Marine pollutant:	Yes Symbol (fish and tree)
Special marking (ADR/RID/ADN):	Symbol (fish and tree)
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30 F F C F
EMS Number:	F-E, <u>S-E</u> A
Stowage Category	A
14.7 Transport in bulk according to Annex II of	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	Tansport classification ADR/IMGD is based on packaging
	>30ltr(IMDG), <450ltr(ADR).
	For other packaging untis different classification ca
	apply.
· ADR/RID/ADN	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E
· IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
• • • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1139 COATING SOLUTION, 3, III
3	ENVIRONMENTALLY HAZARDOUS

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

2 GHS07

GHS09

- · Signal word Warning
- · Hazard-determining components of labelling:

Solvent naphtha (petroleum), light arom. alkanes, C14-17, chloro

Xylene, mixed isomers, pure

· Hazard statements

H226 Flammable liquid and vapour.

H362 May cause harm to breast-fed children.

(Contd. on page 10)

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

(Contd. of page 9)

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· Precautionary statements

P243 Take action to prevent static discharges.

P263 Avoid contact during pregnancy and while nursing.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · Directive 2012/18/EU
- $\cdot \textit{Named dangerous substances-ANNEX I} \ \textit{None of the ingredients is listed}.$
- · Seveso category

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

- · Qualifying quantity (tonnes) for the application of lower-tier requirements 200 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Technical instructions (air):

Class	Share in %
Wasser	0.1
I	6.9
III	0.8
NK	43.9

- · Waterhazard class: Water hazard class 2 (Self-assessment): hazardous for water.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Product safety department.

(Contd. on page 11)

Printing date 06.12.2021 Version number 8 Revision: 06.12.2021

Trade name: FOSTER 60-90

(Contd. of page 10)

· Contact: temati@temati.com

· Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Carc. 2: Carcinogenicity – Category 2

Lact.: Reproductive toxicity – effects on or via lactation

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2