

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.04.2023	100000018445	Date of first issue: 23.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier		
Trade name	:	Foster™ 81-82 comp. A
Product code	:	Foster™ 81-82 comp. A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	: Adhesive	
Recommended restrictions on use	: For industrial use only.	

1.3 Details of the supplier of the safety data sheet

Company	:	H.B. Fuller, Isar-Rakoll, S.A.
Address	:	Estrada Nacional 13 PT-4486-851 Mindelo - Vila do Conde +351 229 288 200
Telephone	:	+448883513523
Telefax	:	+448005286079
E-mail address of person responsible for the SDS	:	EU-MSDS@hbfuller.com
		Distributed By:

Temati Rijnland 2 1948 RL Beverwijk The Netherlands

Phone: +31 (0) 251 22 91 72

1.4 Emergency telephone number

Emergency telephone number : +44 1235 239 670 (24 hours)



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.04.2023	100000018445	Date of first issue: 23.04.2023

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Eye irritation, Category 2


H319: Causes serious eye irritation.

Acute toxicity, Category 4

H332: Harmful if inhaled.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)



Additional Labelling

EUH208 Contains 3,3'-iminodi(propylamine). May produce an allergic reaction.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.04.2023	10000018445	Date of first issue: 23.04.2023

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No.	Classification	Concentration
Chemical hame	EC-No.	Classification	(% w/w)
	Index-No.		(70 007 00)
a a la investa a sui a la	Registration number	A suite Taur 4: 11000	4 0
calcium oxide	1305-78-8	Acute Tox. 4; H302	>= 1 - < 3
	215-138-9	Skin Irrit. 2; H315	
	01-2119475325-36-	Eye Dam. 1; H318	
	0000	STOT SE 3; H335	
		(Respiratory sys-	
		tem)	
3,3'-iminodi(propylamine)	56-18-8	Acute Tox. 4; H302	< 1
	200-261-2	Acute Tox. 2; H330	
	612-063-00-7	Acute Tox. 3; H311	
		Skin Corr. 1A;	
		H314	
		Eye Dam. 1; H318	
		Skin Sens. 1; H317	
Substances with a workplace exposur	e limit :		1
quartz (SiO2)	14808-60-7	STOT RE 2; H373	>= 1 - < 10
	238-878-4	(Lungs)	

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
If inhaled	 Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of unconsciousness bring patient into stable side position for transport.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version 1.0	Revision Date: 23.04.2023	SDS Number: 100000018445	Date of last issue: - Date of first issue: 23.04.2023	
In cas	e of skin contact	: If skin irritatior	n persists, call a physician.	
In case of eye contact		: Flush eyes with water at least 15 minutes. Get medical atten- tion if eye irritation develops or persists.		
If swallowed		Rinse mouth v If conscious, c Do NOT induc	Irink plenty of water.	
4.2 Most in	nportant symptoms a	and effects, both ad	cute and delayed	

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No f

: No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media	:	Use extinguishing measures that are appropriate to local cir- cumstances and the surrounding environment.
		Water mist
		Foam
		Dry powder
		Carbon dioxide (CO2)

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-	:	No further relevant information available.
fighting		

5.3 Advice for firefighters

Special protective equipment for firefighters	:	No special protective measures against fire required.
Further information	:	In the event of fire, wear self-contained breathing apparatus. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version 1.0	Revision Date: 23.04.2023	SDS Number: 100000018445	Date of last issue: - Date of first issue: 23.04.2023
SECTIO	N 6: Accidental relea	se measures	
6.1 Perso	nal precautions, prote	ctive equipment and	d emergency procedures
Perso	onal precautions	: Use personal p Ensure adequa	rotective equipment. te ventilation.
6.2 Envir	onmental precautions		
Envir	onmental precautions	courses or the s	ontaminates rivers and lakes or drains inform
6.3 Metho	ods and material for co	ontainment and clear	ning up
Meth	ods for cleaning up	Soak up with in acid binder, uni	te ventilation. ery or disposal in suitable containers. ert absorbent material (e.g. sand, silica gel, versal binder, sawdust). caminated material as waste according to sec-

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Avoid formation of dust and aerosols. Use only with adequate ventilation. Handle with care. Keep eye wash bottle available on working place. Avoid release to the environment. Keep away from children.
Advice on protection against fire and explosion	:	In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Keep dark, cool and dry. Do not freeze.
Further information on stor- age conditions	:	Keep container tightly sealed. Store in a cool place. Heat will increase pressure and may lead to the container exploding.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.04.2023	10000018445	Date of first issue: 23.04.2023

7.3 Specific end use(s)

Specific use(s)

: No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
quartz (SiO2)	14808-60-7	TWA (Respirable dust)	0,1 mg/m3	GB EH40
	halable dust a sampling is ur MDHS14/4 Ge ble, thoracic a hazardous to in air equal to mg.m-3 8-hou ject to COSHI have been as the appropriat of sizes. The I entry into the depend on the fractions for lin ble dust appro- and mouth du respiratory tra to the gas exc material are g their own assi	are those fractions of indertaken in accorda eneral methods for s and inhalable aeroso health includes dust or greater than 10 n ar TWA of respirable H if people are exposision signed specific WEL te limits., Most indust behaviour, deposition human respiratory size anature and size of mit-setting purposes oximates to the fraction ring breathing and is acc. Respirable dust a change region of the iven in MDHS14/4., igned WEL, all the respiration	ses of these limits, respirable airborne dust which will be of ance with the methods descri ampling and gravimetric ana s., The COSHH definition of of any kind when present at ng.m-3 8-hour TWA of inhala dust. This means that any du sed to dust above these level s and exposure to these must rial dusts contain particles of n and fate of any particular p ystem, and the body respons the particle. HSE distinguished termed 'inhalable' and 'respi on of airborne material that es therefore available for depo approximates to the fraction t lung. Fuller definitions and e Where dusts contain compor elevant limits should be comp osure limit is listed, a figure the used.	collected when bed in lysis or respira- a substance a concentration ble dust or 4 ust will be sub- ls. Some dusts st comply with f a wide range article after se that it elicits, es two size rable'., Inhala- enters the nose sition in the hat penetrates xplanatory nents that have blied with.,
		TWA (Respirable dust)	0,1 mg/m3 (Silica)	GB EH40
	halable dust a sampling is ur MDHS14/4 G ble, thoracic a hazardous to in air equal to	are those fractions of indertaken in accorda eneral methods for s and inhalable aeroso health includes dust or greater than 10 n	ses of these limits, respirable airborne dust which will be of ince with the methods descri ampling and gravimetric ana s., The COSHH definition of of any kind when present at ng.m-3 8-hour TWA of inhala dust. This means that any de	collected when bed in lysis or respira- a substance a concentration ble dust or 4



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version 1.0	Revision Date: 23.04.2023			Date of last issue: - Date of first issue: 23.04.2023				
	ha th of er de fra blu ar re to m th W	ave been as e appropriat sizes. The b atry into the epend on the actions for line e dust appro- nd mouth du spiratory tra the gas exc aterial are g eir own assi here no spe	to COSHH if people are exposed to dust above these levels. Some dusts re been assigned specific WELs and exposure to these must comply with appropriate limits., Most industrial dusts contain particles of a wide range sizes. The behaviour, deposition and fate of any particular particle after ry into the human respiratory system, and the body response that it elicits, beend on the nature and size of the particle. HSE distinguishes two size ctions for limit-setting purposes termed 'inhalable' and 'respirable'., Inhala- dust approximates to the fraction of airborne material that enters the nose I mouth during breathing and is therefore available for deposition in the piratory tract. Respirable dust approximates to the fraction that penetrates the gas exchange region of the lung. Fuller definitions and explanatory terial are given in MDHS14/4., Where dusts contain components that have r own assigned WEL, all the relevant limits should be complied with., ere no specific short-term exposure limit is listed, a figure three times the g-term exposure limit should be used.					
calciu	m oxide 13	805-78-8	TWA	2 mg/m3	GB EH40			
			TWA (Respirable fraction)	1 mg/m3	GB EH40			
			STEL (Respira- ble fraction)	4 mg/m3	GB EH40			
			TWA (Respirable fraction)	1 mg/m3	2017/164/EU			
	Fu	Further information: Indicative						
			STEL (Respira- ble fraction)	4 mg/m3	2017/164/EU			
	Fu	urther inform	ation: Indicative					

8.2 Exposure controls

Engineering measures

Please take care on national and local requirements.

Personal protective equipme Eye protection		Tightly fitting safety goggles
Hand protection Material :		Nitrile rubber
Remarks	:	The glove material has to be impermeable and resistant to the product/the substance/the preparation. The exact break through time can be obtained from the protective glove pro- ducer and this has to be observed.
Skin and body protection	:	Protective clothing
Respiratory protection	:	Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recom-



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version 1.0	Revision Date: 23.04.2023	SDS Number: 100000018445	Date of last issue: - Date of first issue: 23.04.2023
		use breathing f In case of inter	ure guidelines. exposure or low pollution (exceeding of TLV) filter apparatus. nsive or longer exposure use breathing appa- dependent of circulating air.
Protective measures		Instantly remov Wash hands be product. Avoid contact v	m food, drink and animal feedingstuffs. ve any soiled and impregnated garments. efore breaks and immediately after handling the with the eyes and skin. e clothing separately.

Environmental	exposure controls
---------------	-------------------

Air

:	Suppress (knock down) gases/vapours/mists with a water
	spray jet.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	paste
Colour	:	grey
Odour	:	characteristic
Odour Threshold	:	is not determined
рН	:	neutral
Melting point/freezing point	:	is not determined
Initial boiling point and boiling range	:	313 °C
Flash point	:	Not applicable
Evaporation rate	:	is not determined
Flammability (solid, gas)	:	Not classified as a flammability hazard
Upper explosion limit / Upper flammability limit	:	Upper explosion limit is not determined
Lower explosion limit / Lower flammability limit	:	Lower explosion limit is not determined



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Versi 1.0	ion	Revision Date: 23.04.2023		S Number: 0000018445	Date of last issue: - Date of first issue: 23.04.2023
Vapour pressure		:	< 1 hPa		
	Relativ	e vapour density	:	is not determined	1
	Density	/	:	1,43 g/cm³ (20 °0	C)
	Solubili Wat	ty(ies) er solubility	:	not miscible or d	fficult to mix
	Partition coefficient: n- octanol/water		:	no data available	
	Auto-ignition temperature		:	> 450 °C	
	Decom	position temperature	:	Not applicable	
	Explosi	ve properties	:	Not explosive	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions	: None known.

10.4 Conditions to avoid

Conditions to avoid : No further relevant information available.

10.5 Incompatible materials

Materials to avoid : No further relevant information available.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster[™] 81-82 comp. A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.04.2023	10000018445	Date of first issue: 23.04.2023

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity		Based on available data, the classification criteria are not met.
Nouce or an toxion y	•	
		Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method
		Method. Calculation method
Acute inhalation toxicity	:	Harmful by inhalation.
		Acute toxicity estimate: 15 mg/l
		Exposure time: 4 Hours
		Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Based on available data, the classification criteria are not met.
		Acute toxicity estimate: > 2.000 mg/kg
		Method: Calculation method
Componentes		
<u>Components:</u>		
3,3'-iminodi(propylamine):		
A suite industriant toxisity		$L \subseteq Q $ (Bot): $Q = Q = math$

Acute inhalation toxicity	:	LC50 (Rat): 0,03 mg/l
		Exposure time: 4 Hours

SECTION 12: Ecological information

12.1 Toxicity <u>Components:</u> calcium oxide: Toxicity to fish : LC50 (Cyprinus carpio (Carp)): 1.070 mg/l Exposure time: 96 Hours Test Type: static test

12.2 Persistence and degradability

No data available



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version 1.0	Revision Date: 23.04.2023	SDS Number: 100000018445	Date of last issue: - Date of first issue: 23.04.2023		
12.3 Bioa	ccumulative potentia	I			
No da	ata available				
12.4 Mobi	ility in soil				
<u>Prod</u>	uct:				
Mobil	lity	: Medium: Soil Remarks: Do r bodies or sewa	not allow product to reach ground water, water age system.		
12.5 Resu	Ilts of PBT and vPvB	assessment			
Prod	uct:				
Asse	ssment	to be either pe very persisten	: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.		
12.6 Othe	r adverse effects				
No da	ata available				
SECTION	N 13: Disposal cons	siderations			
13.1 Wast	te treatment methods	5			
Produ	uct	Do not dispose Hand over to o Can be depos following cons facility and the the necessary The generation wherever poss	e of with domestic refuse. e of waste into sewer. disposers of hazardous waste. ited with household garbage after solidification ultation with the operator of the waste disposal e pertinent authorities and under adherence to technical regulations. n of waste should be avoided or minimized sible. er controlled conditions in accordance with all		

Contaminated packaging : Disposal must be made according to official regulations.

local and national laws and regulations.

Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	23.04.2023	10000018445	Date of first issue: 23.04.2023

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
RoHS: 2011/65/EU, Restriction of Hazardous Substances	:	Not applicable
Council Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors	:	Neither banned nor restricted
Regulation (EC) No 649/2012 of the European Parlia- ment and the Council concerning the export and import of dangerous chemicals	:	Not applicable



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version 1.0	Revision Date: 23.04.2023	SDS Number: 100000018445	Date of last issue: - Date of first issue: 23.04.2023
UK RE (Anne:	EACH List of substance x XIV)	s subject to autho	risation : Not applicable
	o III: Directive 2012/18 accident hazards involv		
Volatil	e organic compounds		10/75/EU of 24 November 2010 on industrial ntegrated pollution prevention and control) le
	•	•	d in the following inventories:
REAC	Н	: On the inver	tory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements		
H302	:	Harmful if swallowed.
H311	:	Toxic in contact with skin.
H314	:	Causes severe skin burns and eye damage.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H330	:	Fatal if inhaled.
H335	:	May cause respiratory irritation.
H373	:	May cause damage to organs through prolonged or repeated
		exposure.
Full text of other abbreviation	ns	
Acute Tox.	:	Acute toxicity
Eye Dam.	:	Serious eye damage
Skin Corr.	:	Skin corrosion
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure
STOT SE	:	Specific target organ toxicity - single exposure
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a
		fourth list of indicative occupational exposure limit values
	:	UK. EH40 WEL - Workplace Exposure Limits
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version	Revision Date: 23.04.2023	SDS Number:	Date of last issue: -
1.0		100000018445	Date of first issue: 23.04.2023
GB E	H40 / TWA	: Long-term exp	osure limit (8-hour TWA reference period

GB EH40 / TWA:Long-term exposure limit (8-hour TWA reference period)GB EH40 / STEL:Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIOC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information	safet	safety datasheet only contains information relating to y and does not replace any product information or prod- pecification.	
Contact Point		Prepared by: Global Regulatory Department EU-MSDS@hbfuller.com	
Classification of the mixture	:	Classification procedure:	
Eye Irrit. 2	H319	Calculation method	



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. A

Version 1.0	Revision Date: 23.04.2023	SDS Number: 100000018445	Date of last issue: - Date of first issue: 23.04.2023
Acute	Tox. 4	H332	Calculation method
Acute	Tox. 4	H332	Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023	SDS Number: 100000025597	Date of last issue: 23.04.2023 Date of first issue: 23.04.2023
SECTION	N 1: Identification of	the substance	/mixture and of the company/undertaking
1.1 Produ	ıct identifier		
Trade	e name	: Foster™ 81	-82 comp. B
Subs	tance name		ethanediisocyanate, isomeres and homologues per: 9016-87-9)
1.2 Relev	ant identified uses of t	he substance o	r mixture and uses advised against
	of the Sub- ce/Mixture	: Hardener /	Curing agent
Reco on us	mmended restrictions	: For industri	al use only.
1.3 Detail	s of the supplier of the	e safety data she	et
Com	pany	: H.B. Fuller,	Isar-Rakoll, S.A.
Addre	ess	: Estrada Na PT-4486-85 +351 229 2	51 Mindelo - Vila do Conde
Telep	phone	: +44888351	3523
Telef	ax	: +44800528	6079
	ail address of person onsible for the SDS	: EU-MSDS@	⊉hbfuller.com
		Distribute	d By:
		Temati Rijnland 2 1948 RL B The Nethe	
		Phone: +3	1 (0) 251 22 91 72
1.4 Emer	gency telephone numb	ber	
-	rgency telephone number		239 670 (24 hours)



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster[™] 81-82 comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2023
1.1	25.04.2023	10000025597	Date of first issue: 23.04.2023

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Acute toxicity, Category 4	H332: Harmful if inhaled.
Carcinogenicity, Category 2	H351: Suspected of causing cancer.
Specific target organ toxicity - single ex- posure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Respiratory sensitisation, Category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through pro- longed or repeated exposure.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :		
Signal word :	Dang	jer
Hazard statements :	H334	 May cause an allergic skin reaction. Causes serious eye irritation. Harmful if inhaled. May cause allergy or asthma symptoms or breathing ulties if inhaled. May cause respiratory irritation.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023	SDS Number: 100000025597	Date of last issue: 23.04.2023 Date of first issue: 23.04.2023
		H373 May cau repeated exposu	se damage to organs through prolonged or re.
Preca	utionary statements	P280 Wear pro	reathe dust/ fume/ gas/ mist/ vapours/ spray. otective gloves/ protective clothing/ eye protec- ion/ hearing protection.
			P338 IF IN EYES: Rinse cautiously with wa- inutes. Remove contact lenses, if present and inue rinsing.
		Storage: P403 + P233 S tightly closed. P405 Store loo	Store in a well-ventilated place. Keep container
			of contents/ container to an approved facility in local, regional, national and international regu-
Addit	ional Labelling		

EUH204 Contains isocyanates. May produce an allergic reaction. "As from 24 August 2023 adequate training is required before industrial or professional use."

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Substance name : Diphenylmethanediisocyanate, isomeres and homologues (CAS Number: 9016-87-9)

Components

Chemical name	CAS-No. EC-No.	Concentration (% w/w)
Diphenylmethanediisocya- nate, polymeric	9016-87-9	>= 90 - <= 100



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023	SDS Number: 100000025597	Date of last issue: 23.04.2023 Date of first issue: 23.04.2023	

SECTION 4: First aid measures

4.1 Description of first aid measure	es
General advice :	Immediately remove clothing if soiled by product.
	Even minimal concentrations of isocyanate can lead to a reac- tion in sensitised people. Symptoms that may occur include the following: irritation of the eyes, nose, throat and lungs, possibly together with a dry throat, a feeling of chest tightness and breathing difficulties.
	Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident. Show this safety data sheet to the doctor in attendance.
If inhaled :	Remove person to fresh air. If signs/symptoms continue, get medical attention. In case of unconsciousness bring patient into stable side posi- tion for transport.
In case of skin contact :	Treat affected skin with cotton wool or cellulose. Wash off immediately with plenty of water. Use a mild soap if available. If symptoms persist, call a physician.
In case of eye contact :	Flush eyes with water at least 15 minutes. Get medical atten- tion if eye irritation develops or persists.
If swallowed :	If accidentally swallowed obtain immediate medical attention. Do NOT induce vomiting. If symptoms persist, call a physician.
4.2 Most important symptoms and None known.	effects, both acute and delayed
-	edical attention and special treatment needed
Treatment :	In instances of existing sensitisation towards isocyanates, a doctor should be consulted with regards to work-related con- tact with other sensitising substances, or substances which irritate the airway.
	Treatment for exposure should be geared towards monitoring

symptoms and the patient's clinical condition.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023		DS Number: 00000025597	Date of last issue: 23.04.2023 Date of first issue: 23.04.2023
			It must be ensi and oxygen su	ured that the patient has sufficient ventilation pply.
			ma-like sympto	an cause sensitisation of the airways, or asth- oms (bronchospasms). Delayed breathing luding lung oedema, may occur.
		People who have shown signs of breathlessness after consid- erable exposure should remain under observation for 24-48 hours.		
SECTION	N 5: Firefighting mea	sui	es	
5.1 Exting	guishing media			
Suita	ble extinguishing media	:	•	ing measures that are appropriate to local cir- nd the surrounding environment. nt foam

		Carbon dioxide (CO2)
Unsuitable extinguishing media	:	Water with a full water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire- fighting	:	May release toxic, irritating and/or corrosive gases. In case of fire CO, NOx, isocyanates and traces of HCN can be formed.

5.3 Advice for firefighters

Special protective equipment for firefighters	:	Wear an approved positive pressure self-contained breathing apparatus in addition to standard fire fighting gear.
Further information	:	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Use personal protective equipment. Use breathing protection against the effects of fumes/dust/aerosol. Evacuate personnel to safe areas. Ensure adequate ventilation.
----------------------	---



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2023
1.1	25.04.2023	10000025597	Date of first issue: 23.04.2023

6.2 Environmental precautions

Environmental precautions	cautions :	The product should not be allowed to enter drains, water courses or the soil.
		If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Non-sparking tools should be used. Ensure adequate ventilation. Send for recovery or disposal in suitable containers. Dispose of contaminated material as waste according to sec- tion 13.
-------------------------	---	---

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling	:	Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the vapor concentration below the work- place limit, wear an adequate respiratory protective device. Take note of emission threshold. Avoid formation of aerosol. Do not heat the product. Ensure that suitable extractors are available on processing machines. Handle with care. Avoid inhalation and skin contact. Keep eye wash bottle available on working place. Avoid release to the environment. Keep away from children.
Advice on protection against fire and explosion	:	In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage	:	Keep dark, cool and dry. Do not freeze.
areas and containers		



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023		DS Number: 0000025597	Date of last issue: 23.04.2023 Date of first issue: 23.04.2023
	er information on stor- onditions	:	Keep containers ventilated place.	tightly closed in a dry, cool and well-
Advic	e on common storage	:	Keep away from	food, drink and animal feedingstuffs.
Damp	oness	:	Keep containers sorption and cont	dry and tightly closed to avoid moisture ab- amination.
	f ic end use(s) ific use(s)	:	No further releva	nt information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Diphenylme- thanediisocyanate, polymeric	9016-87-9	TWA	0,02 mg/m3 (as -NCO)	GB EH40
	known as asth cific airway hy anism. Once t the substance symptoms. Th asthma. Not a responsive an become hyper should be dist asthma in peo not include the as asthmagen the HSE publi agents implica cable, exposu prevented. WI standards of c substances th sure be reduc short-term pea management employees ex occupational a	magens and respirate per-responsiveness he airways have been sometimes even in lese symptoms can all workers who are end it is impossible to r-responsive. Substi- inguished from substi- ple with pre-existing endisease themselve as or respiratory sense cation Asthmagen? ated in occupational re to substances that here this is not possi- control to prevent wo at can cause occupate end to as low as is re- ak concentrations sh is being considered. posed or liable to be asthma and there sh	hat can cause occupational a tory sensitisers) can induce via an immunological irritant come hyper-responsive, furth tiny quantities, may cause r range in severity from a runn xposed to a sensitiser will be identify in advance those which tances that can cause occup tances which may trigger the airway hyper-responsivenes s. The latter substances are sitisers. Further information of Critical assessments of the e asthma., Wherever it is rease t can cause occupational as ble, the primary aim is to appr kers from becoming hyper-re ational asthma, COSHH requ asonably practicable. Activiti ould receive particular attent Health surveillance is appro- exposed to a substance who ould be appropriate consulta ver the degree of risk and le	a state of spe- or other mech- her exposure to espiratory y nose to ecome hyper- o are likely to ational asthma e symptoms of ss, but which do not classified can be found in evidence for onably practi- thma should be oly adequate responsive. For nires that expo- es giving rise to cion when risk priate for all ich may cause tion with an



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

/ersion 1.1	Revision Date 25.04.2023		Number: 00025597	Date of last issue: 23.0 Date of first issue: 23.0	
		of WELs has to pational asthm that other sub-	been assigned on the catego stances not in t	ccupational asthma., The only to those substances vries shown in Table 1. It s hese tables may cause or ww.hse.gov.uk/asthma) p 0,07 mg/m3	which may cause occu- should be remembered ccupational asthma.
			OTEL	(as -NCO)	
		known as asth cific airway hy anism. Once t the substance symptoms. Th asthma. Not a responsive an become hyper should be dist asthma in peo not include the as asthmagen the HSE publi agents implica cable, exposu prevented. Wh standards of c substances th sure be reduc short-term pea management employees ex occupational a boccupational a tance., Capab of WELs has t pational asthm that other sub-	imagens and re per-responsive he airways have , sometimes ev lese symptoms Il workers who d it is impossible -responsive. S inguished from ple with pre-exi- e disease thems is or respiratory cation Asthmag ated in occupati- re to substance here this is not p- control to prever at can cause of ed to as low as ak concentration is being conside posed or liable asthma and the health profession le of causing of posen assigned on a in the categor stances not in t	ces that can cause occupations is preserved an immunological e become hyper-responsion in tiny quantities, may can range in severity from are exposed to a sensitise to identify in advance the Substances that can caus substances which may triasting airway hyper-responsional asthma., Wherever it is that can cause occupational asthma, COS is reasonably practicable as should receive particulate should be appropriate of nal over the degree of rist cause asthma., The only to those substances is shown in Table 1. It is hese tables may cause occupational asthma., The only to those substances of the degree of rist cause asthma., The only to those substances of the degree of rist cause asthma. The only to those substances of the degree of rist cause asthma. The only to those substances of the degree of rist cause tables may cause of the tables may cause of	induce a state of spe- al irritant or other mech ve, further exposure to cause respiratory n a runny nose to er will become hyper- nose who are likely to e occupational asthma gger the symptoms of nsiveness, but which do ces are not classified mation can be found in of the evidence for t is reasonably practi- ional asthma should be is to apply adequate hyper-responsive. For HH requires that expo- . Activities giving rise to ar attention when risk is appropriate for all ance which may cause consultation with an k and level of surveil- 'Sen' notation in the list which may cause occu should be remembered ccupational asthma.
			IVVA	(NCO)	
		known as asth cific airway hy anism. Once t the substance symptoms. Th	magens and re per-responsive he airways hav , sometimes ev lese symptoms	ces that can cause occupa espiratory sensitisers) can ness via an immunologica e become hyper-responsi en in tiny quantities, may can range in severity from are exposed to a sensitise	induce a state of spe- al irritant or other mech ve, further exposure to cause respiratory n a runny nose to



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023		Number: 00025597		last issue: 23.04.2 first issue: 23.04.2		
	be sh as no as the ag ca pre sta su su su su sh ma er oc oc lar of pa tha HS	responsive and it is impossible to identify in advance those who are likely t become hyper-responsive. Substances that can cause occupational asthr should be distinguished from substances which may trigger the symptoms asthma in people with pre-existing airway hyper-responsiveness, but which not include the disease themselves. The latter substances are not classifie as asthmagens or respiratory sensitisers. Further information can be found the HSE publication Asthmagen? Critical assessments of the evidence for agents implicated in occupational asthma., Wherever it is reasonably pract cable, exposure to substances that can cause occupational asthma should prevented. Where this is not possible, the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive. I substances that can cause occupational asthma, COSHH requires that exp sure be reduced to as low as is reasonably practicable. Activities giving riss short-term peak concentrations should receive particular attention when ris management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cau occupational asthma and there should be appropriate consultation with an occupational asthma and there should be appropriate consultation with an occupational asthma in the categories shown in Table 1. It should be remember that other substances not in these tables may cause occupational asthma. HSE's asthma web pages (www.hse.gov.uk/asthma) provide further infor- mation.					
			STEL	0,07 (NC	7 mg/m3 :O)	GB EH40	
	known as asthr cific airway hyp anism. Once th the substance, symptoms. The asthma. Not all responsive and become hyper- should be distin asthma in peop not include the as asthmagens the HSE public agents implicat cable, exposure prevented. Wh standards of co substances tha sure be reduce short-term peal		imagens and per-responsiv he airways ha , sometimes e lese symptom Il workers who d it is impossive. inguished from ple with pre-e e disease ther is or respirato cation Asthma ated in occupation re to substant pere this is no control to preve at can cause ed to as low a ak concentrati	nces that ca respiratory : eness via a ve become even in tiny s can range o are expos ble to identi Substance n substance xisting airw nselves. Th ry sensitise agen? Critic tional asthr ces that can t possible, t ent workers occupationa s is reasona ons should	an cause occupati sensitisers) can in n immunological i hyper-responsive quantities, may ca e in severity from a ed to a sensitiser fy in advance those s that can cause of es which may trigg ay hyper-respons e latter substance rs. Further informa- al assessments of na., Wherever it is cause occupation he primary aim is from becoming h al asthma, COSHI ably practicable. A		



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2023
1.1	25.04.2023	100000025597	Date of first issue: 23.04.2023
	occup occup lance of WE pation that o	bational asthma and the bational health profession ., Capable of causing of ELs has been assigned hal asthma in the categorither substances not in a asthma web pages (N	e to be exposed to a substance which may cause ere should be appropriate consultation with an onal over the degree of risk and level of surveil- occupational asthma., The 'Sen' notation in the list only to those substances which may cause occu- pories shown in Table 1. It should be remembered these tables may cause occupational asthma. www.hse.gov.uk/asthma) provide further infor-

8.2 Exposure controls

Engineering measures

Please take care on national and local requirements.

:

Personal protective equipment

Eye protection

Tightly fitting safety goggles

Hand protection

Remarks

: Direct contact with the isocyanate-based product must be avoided by organizational measures.

The glove material has to be impermeable and resistant to the product/the substance/the preparation. The exact break through time can be obtained from the protective glove producer and this has to be observed.

The gloves need to be disposed after the penetration time and replaced by new ones.

Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Butyl rubber (minimum thickness: 0.7 mm; penetration time:



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023	-	DS Number: 00000025597	Date of last issue: 23.04.2023 Date of first issue: 23.04.2023
			15 min)	
			ing materials are	om splashes gloves made of the follow- e suitable: ickness 0.12 mm), Disposable gloves with
				the chemical preparation, take the dispos- off immediately and put on a new disposable
Skin	and body protection	:	Protective clothing	g
			with the isocyana maintenance wor	It activities where unintentional skin contact te-based product may occur (e.g. during k, or when opening a barrel), wear long- e clothing and gloves.
Resp	Respiratory protection		Use respiratory protection unless adequate risk manageme measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recom mended exposure guidelines. In case of brief exposure or low pollution (exceeding of TLV use breathing filter apparatus. In case of intensive or longer exposure use breathing appa- ratus that is independent of circulating air.	
Fi	lter type	:	For short term use late filter is recom	e a combination of charcoal filter and particu- mended.
Prote	ctive measures	:	Wash hands befo product. Avoid contact with Store protective c	any soiled and impregnated garments. re breaks and immediately after handling the n the eyes and skin. dothing separately. food, drink and animal feedingstuffs.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	:	liquid
Colour	:	amber
Odour	:	unpleasant



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023		S Number: 0000025597	Date of last issue: 23.04.2023 Date of first issue: 23.04.2023
Odou	ır Threshold	:	is not determined	I
pН		:	neutral	
Melti	ng point/freezing point	:	41 °C	
Initia range	l boiling point and boiling e	:	190 °Cis not dete	ermined
Flash	n point	:	> 200 °C	
Evap	oration rate	:	is not determined	I
Vapo	our pressure	:	0,0002 hPa (25 °	C)
Relat	tive vapour density	:	is not determined	I
Dens	ity	:	1,23 g/cm³ (20 °0	2)
	bility(ies) /ater solubility	:	reacts with water	
	tion coefficient: n- nol/water	:	no data available	
Auto	ignition temperature	:	400 °C	
Deco	mposition temperature	:	Not applicable	
Visco Vi	osity iscosity, dynamic	:	180 - 260 mPa.s	(20 °C)
Explo	osive properties		Not explosive	

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023	SDS Number: 100000025597	Date of last issue: 23.04.2023 Date of first issue: 23.04.2023
Haza	rdous reactions	Mixture read Evolution of	alcohols, amines, aqueous acids and alkalis. ets with water resulting in evolution of CO2. CO2 in closed containers causes overpressure es a risk of bursting.
10.4 Cond	ditions to avoid		
Cond	itions to avoid	: No further re	elevant information available.
10.5 Incoi	mpatible materials		
Mate	rials to avoid	: No further re	elevant information available.
10.6 Haza	rdous decompositio	n products	
Nitrog	se of fire hazardous de gen oxides (NOx) anates	ecomposition produc	ts may be produced such as:

Additional information: Open and release pressure carefully with pressurised containers.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:		
Acute oral toxicity	:	Based on available data, the classification criteria are not met.
Acute inhalation toxicity	:	Based on available data, the classification criteria are not met.
Acute dermal toxicity	:	Based on available data, the classification criteria are not met.

Components:

Diphenylmethanediisocyanate, polymeric:

Acute inhalation toxicity	:	LC50 (Rat): 0,49 mg/l Exposure time: 4 Hours Test atmosphere: dust/mist	

Acute toxicity estimate: 1,5 mg/l Test atmosphere: dust/mist Method: Calculation method



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster[™] 81-82 comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2023
1.1	25.04.2023	10000025597	Date of first issue: 23.04.2023

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

Product:

Mobility

: Medium: Soil Remarks: Do not allow product to reach ground water, water bodies or sewage system.

12.5 Results of PBT and vPvB assessment

Product:

Assessment

: This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods		
Product	:	Do not dispose of with domestic refuse. Do not dispose of waste into sewer. Hand over to disposers of hazardous waste. The generation of waste should be avoided or minimized wherever possible. Incinerate under controlled conditions in accordance with all local and national laws and regulations. Disposal must be made according to official regulations.
Contaminated packaging	:	Disposal must be made according to official regulations.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster[™] 81-82 comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2023
1.1	25.04.2023	10000025597	Date of first issue: 23.04.2023

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)	:	Conditions of restriction for the fol- lowing entries should be considered: Number on list 3
		Diphenylmethanediisocyanate, pol- ymeric (Number on list 74)
REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollu- tants (recast)	:	Not applicable
RoHS: 2011/65/EU, Restriction of Hazardous Substances	:	Not applicable



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster[™] 81-82 comp. B

Version 1.1	Revision Date: 25.04.2023	SDS Number: 100000025597	Date of last issue: 23.04.2023 Date of first issue: 23.04.2023
for the	cil Regulation (EC) No e monitoring of trade be countries in drug precur	etween the Community	
ment	lation (EC) No 649/201 and the Council concer ngerous chemicals		
	EACH List of substance ex XIV)	es subject to authorisa	tion : Not applicable
	so III: Directive 2012/18 r-accident hazards invol		Parliament and of the Council on the control of ances.
Volati	ile organic compounds		5/EU of 24 November 2010 on industrial rated pollution prevention and control)
The c	components of this pr	oduct are reported ir	the following inventories:
REAC	СН	: On the inventor	v, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of other abbreviations

GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships car-



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 81-82 comp. B

Version	Revision Date:	SDS Number:	Date of last issue: 23.04.2023
1.1	25.04.2023	10000025597	Date of first issue: 23.04.2023

rying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information	:	This safety datasheet only contains information relating to safety and does not replace any product information or product specification.
Contact Point	:	Prepared by: Global Regulatory Department EU-MSDS@hbfuller.com

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN