



TEMTEX™ T1050/HT750



Description	A heavy duty welding fabric treated with a special inorganic finish to improve the temperature- and burn-through resistance of the fabric.			
Applications	- Heavy duty welding blankets - Welders pads		- Heavy duty welding curtains - Annealing covers	
Approvals				
Characteristics of Temtex T1050/HT750				Test method
Total weight	g / m ²	1120	± 5%	
Width (std)	mm	1000	± 15	DIN EN 1773
Thickness	mm	1.50	± 0.1	
Roll length (std)	m	50		
Max. application temperature	°C	750		
Remarks				

Fabric structure				
	Unit	Data	Tolerance	Test method
Base fabric		E-Glass		
Weight	g / m ²	1050	± 5%	DIN EN 12127
Weave		Panama 2/2		
Setting	per cm	11.2 x 7.2	± 3%	DIN 53853
Warp	Tex	ECT9 T630 006	± 5%	
Weft	Tex	ECT9 T485 006	± 5%	
Tensile strength (warp x weft)	N/cm	3800 x 2400		DIN 53857
Coating / Finish		"HT750"		
Weight	g / m ²	70	± 5%	
1 or 2 sided		Impregnated		

Tensile strength data refers to loomstate fabrics. Stability, thickness and surface weight vary according to the type of fabric finish. The given values are approximate and not guaranteed.