

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1 Product identifier**

Trade name : Foster™ 60-44
Product code : Foster™ 60-44

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Coating
Recommended restrictions : For industrial use only.
on use

1.3 Details of the supplier of the safety data sheet

Company : H.B. Fuller, Isar-Rakoll, S.A.
Address : Estrada Nacional 13
PT-4486-851 Mindelo - Vila do Conde
+351 229 288 200
E-mail address of person
responsible for the SDS : EU-MSDS@hbfuller.com

Distributed By:

Temati
Rijnland 2
1948 RL Beverwijk
The Netherlands

Phone: +31 (0) 251 22 91 72

1.4 Emergency telephone number

Emergency telephone number : +44 1235 239 670 (24 hours)

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 3	H226: Flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :



Signal word : Warning

Hazard statements :

- H226 Flammable liquid and vapour.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H335 May cause respiratory irritation.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

Precautionary statements :

Prevention:

P243 Take action to prevent static discharges.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection/ hearing protection.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved facility in accordance with local, regional, national and international regulations.

Hazardous components which must be listed on the label:

xylenes

Hydrocarbons C9, aromatics

Hydrocarbons, C9-unsatd., polymd.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
xylenes	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32-0000	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Asp. Tox. 1; H304	>= 10 - < 25

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version 2.0 Revision Date: 04.12.2023 SDS Number: 100000018436 Date of last issue: 21.04.2023
Date of first issue: 21.04.2023

		2; H319 STOT SE 3; H335 STOT RE 2; H373	
Hydrocarbons C9, aromatics	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35-0000	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) STOT SE 3; H335 (Respiratory system) Asp. Tox. 1; H304 Aquatic Chronic 2; H411	>= 5 - < 10
Hydrocarbons, C9-unsatd., polymd.	71302-83-5 615-276-3 01-2119555292-40-0000	Skin Sens. 1; H317 Aquatic Chronic 3; H412	>= 5 - < 10
Quaternary ammonium compounds, dicoco alkyl dimethyl, chlorides	61789-77-3 263-087-6 01-2119486994-16-0000	Acute Tox. 4; H302 Skin Corr. 1B; H314 Aquatic Acute 1; H400	< 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : If on clothes, remove clothes.
Move the victim to fresh air.
Show this safety data sheet to the doctor in attendance.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
In case of unconsciousness bring patient into stable side position for transport.
- In case of skin contact : Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
If skin irritation persists, call a physician.
- In case of eye contact : Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

If swallowed : If accidentally swallowed obtain immediate medical attention.
Rinse mouth with water.
If conscious, drink plenty of water.
Do NOT induce vomiting.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

None known.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Water mist
Foam
Dry powder
Carbon dioxide (CO₂)

Unsuitable extinguishing media : Water with a full water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : No further relevant information available.

5.3 Advice for firefighters

Special protective equipment for firefighters : No special protective measures against fire required.

Further information : In the event of fire, wear self-contained breathing apparatus.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Remove all sources of ignition.
Use personal protective equipment.
Use breathing protection against the effects of fumes/dust/aerosol.
Evacuate personnel to safe areas.
Ensure adequate ventilation.

6.2 Environmental precautions

Environmental precautions : The product should not be allowed to enter drains, water courses or the soil.
Prevent the material from reaching sewage system, holes and cellars.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Non-sparking tools should be used.
Ensure adequate ventilation.
Send for recovery or disposal in suitable containers.
Dispose of contaminated material as waste according to section 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8., For disposal considerations see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Avoid formation of dust and aerosols.
Use only with adequate ventilation.
Take note of emission threshold.
Use solvent-proof equipment.
Ensure that suitable extractors are available on processing machines.
Handle with care.
Keep eye wash bottle available on working place.
Avoid release to the environment.
Keep away from children.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

Advice on protection against fire and explosion : Keep product and empty container away from heat and sources of ignition. Do not smoke. Take measures to prevent the build up of electrostatic charge. May form explosive mixtures in air. Highly volatile, flammable constituents are released during processing. In the event of fire and/or explosion do not breathe fumes. Keep breathing equipment ready. Have fire extinguishing equipment ready in case of nearby fire.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep dark, cool and dry. Store in cool place.

Further information on storage conditions : Keep containers tightly closed in a dry, cool and well-ventilated place. Store in a cool place. Heat will increase pressure and may lead to the container exploding.

7.3 Specific end use(s)

Specific use(s) : No further relevant information available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
xylene	1330-20-7	TWA	50 ppm 221 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

Derived No Effect Level (DNEL):

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons C9, aromatics	Workers	Dermal	Long-term systemic effects	25 mg/kg
	Workers	Dermal	Acute systemic effects	25 mg/kg
	Workers	Inhalation	Long-term systemic effects	150 mg/m ³
	Workers	Inhalation	Acute systemic ef-	150 mg/m ³

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

			fects	
--	--	--	-------	--

8.2 Exposure controls

Engineering measures

Please take care on national and local requirements.

Personal protective equipment

Eye protection : Tightly fitting safety goggles

Hand protection

Remarks : The glove material has to be impermeable and resistant to the product/the substance/the preparation.
The exact break through time can be obtained from the protective glove producer and this has to be observed.
The gloves need to be disposed after the penetration time and replaced by new ones.
Apply skin protectant before working with gloves to avoid skin swellings and use a skin cleansing and skincare product after the work.

For the permanent contact gloves made of the following materials are suitable:

If longer exposure to the chemical preparation is necessary, a sturdy overglove against mechanical strain is recommended in combination with the Barrier 02-100 underglove from Ansell or other suppliers (penetration time: 480 min).

For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:

Butyl rubber (minimum thickness: 0.7 mm; penetration time: 15 min)

As protection from splashes gloves made of the following materials are suitable:

Nitril (minimum thickness 0.12 mm), Disposable gloves with long cuffs

After contact with the chemical preparation, take the disposable nitrile glove off immediately and put on a new disposable nitrile glove.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

Skin and body protection	:	Protective clothing
Respiratory protection	:	Use respiratory protection unless adequate risk management measures (exhaust/ ventilation) are provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. In case of brief exposure or low pollution (exceeding of TLV) use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air. Ensure that suitable extractors are available on processing machines.
Protective measures	:	Keep away from food, drink and animal feedingstuffs. Instantly remove any soiled and impregnated garments. Wash hands before breaks and immediately after handling the product. Avoid contact with the eyes and skin. Store protective clothing separately.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties**

Appearance	:	liquid
Colour	:	black
Odour	:	characteristic
Odour Threshold	:	is not determined
pH	:	neutral
Melting point/freezing point	:	is not determined
Initial boiling point and boiling range	:	136 - 145 °C
Flash point	:	23 °C
Evaporation rate	:	is not determined
Upper explosion limit / Upper flammability limit	:	Upper explosion limit 7,1 %(V)
Lower explosion limit / Lower	:	Lower explosion limit

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

flammability limit	:	1 %(V)
Vapour pressure	:	10 hPa (20 °C) 20 hPa (20 °C)
Relative vapour density	:	is not determined
Density	:	1,17 g/cm ³ (20 °C)
Solubility(ies) Water solubility	:	completely miscible
Partition coefficient: n-octanol/water	:	no data available
Auto-ignition temperature	:	450 °C
Decomposition temperature	:	Not applicable
Viscosity Viscosity, dynamic	:	150.000 mPa.s (20 °C)
Viscosity, kinematic	:	> 20,5 mm ² /s (40 °C)
Explosive properties	:	Product is not explosive. However, formation of explosive vapour/air mixtures is possible.

9.2 Other information

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No further relevant information available.

10.2 Chemical stability

No decomposition if used according to the specifications.

10.3 Possibility of hazardous reactions

Hazardous reactions : Develops readily flammable vapours/fumes.

10.4 Conditions to avoid

Conditions to avoid : No further relevant information available.

10.5 Incompatible materials

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

Materials to avoid : No further relevant information available.

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 Hours
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

SECTION 12: Ecological information

12.1 Toxicity

No data available

12.2 Persistence and degradability

No data available

12.3 Bioaccumulative potential

Components:

xylenes:

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15
GLP: no

12.4 Mobility in soil

Product:

Mobility : Medium: Soil
Remarks: Do not allow product to reach ground water, water bodies or sewage system.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Do not dispose of waste into sewer.
Hand over to disposers of hazardous waste.
The generation of waste should be avoided or minimized wherever possible.
Incinerate under controlled conditions in accordance with all local and national laws and regulations.
Disposal must be made according to official regulations.

Contaminated packaging : Disposal must be made according to official regulations.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1139
ADR : UN 1139
RID : UN 1139
IMDG : UN 1139
IATA : UN 1139
Not permitted for transport

14.2 UN proper shipping name

ADN : COATING SOLUTION
ADR : COATING SOLUTION
RID : COATING SOLUTION

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

IMDG : COATING SOLUTION
IATA : COATING SOLUTION
Not permitted for transport

14.3 Transport hazard class(es)

ADN : 3
ADR : 3
RID : 3
IMDG : 3
IATA (Cargo) : 3
IATA_P (Passenger) : Not permitted for transport

14.4 Packing group

ADN
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Remarks : Product is not subject to ADN in containers with a maximum content of 450 litres (according to 2.2.3.1.5.1 ADN)!

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)
Remarks : Product is not subject to ADR in containers with a maximum content of 450 litres (according to 2.2.3.1.5.1 ADR)!

RID
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Remarks : Product is not subject to RID in containers with a maximum content of 450 litres (according to 2.2.3.1.5.1 RID)!

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

Remarks : For containers with a maximum content of 450 litres, the simplified regulations according to 2.3.2.5 IMDG are applicable!

IATA (Cargo) : Not permitted for transport

IATA_P (Passenger) : Not permitted for transport

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
Number on list 3

xylenes

REACH - Candidate List of Substances of Very High Concern for Authorisation (SVHC, Article 59) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

RoHS: 2011/65/EU, Restriction of Hazardous Substances : Not applicable

Council Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors : Neither banned nor restricted

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.
P5c FLAMMABLE LIQUIDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 22,6 %, 264,4 g/l
Not applicable

The components of this product are reported in the following inventories:

REACH : On the inventory, or in compliance with the inventory

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture.

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by
UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

H373 : May cause damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H411 : Toxic to aquatic life with long lasting effects.
H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Asp. Tox. : Aspiration hazard
Flam. Liq. : Flammable liquids
Skin Corr. : Skin corrosion
Skin Irrit. : Skin irritation
Skin Sens. : Skin sensitisation
STOT RE : Specific target organ toxicity - repeated exposure
STOT SE : Specific target organ toxicity - single exposure
2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2000/39/EC / TWA : Limit Value - eight hours
2000/39/EC / STEL : Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous

SAFETY DATA SHEET

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758

Foster™ 60-44

Version	Revision Date:	SDS Number:	Date of last issue: 21.04.2023
2.0	04.12.2023	100000018436	Date of first issue: 21.04.2023

Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information : This safety datasheet only contains information relating to safety and does not replace any product information or product specification.

Modified data compared to the previous version

The following section has been updated:
- Section 14

Contact Point : Prepared by: Global Regulatory Department
EU-MSDS@hbfuller.com

Classification of the mixture:

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
STOT SE 3	H335
STOT RE 2	H373
Aquatic Chronic 3	H412

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN