

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.12.2021

Version number 10

Revision: 06.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: Foster 60-25**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Bitumen coating
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Temati
Rijnland 2
NL-1948 RL Beverwijk
Tel: +31 251 229 172
E-mail: temati@temati.com
- **Further information obtainable from:** Regulatory Department
- **1.4 Emergency telephone number:** +44 (0) 1235 239 670 (24 hrs)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT RE 1 H372 Causes damage to the central nervous system through prolonged or repeated exposure.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
Naphtha (petroleum), hydrodesulfurized heavy
- **Hazard statements**
H226 Flammable liquid and vapour.
H372 Causes damage to the central nervous system through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 06.12.2021

Version number 10

Revision: 06.12.2021

Trade name: Foster 60-25

(Contd. of page 1)

- P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
- P403+P235 Store in a well-ventilated place. Keep cool.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**
- **Description:** Mixture of substances listed below with additions.

- **Dangerous components:**

CAS: 64742-82-1 EC number: 919-446-0 Reg.nr.: 01-2119458049-33	Naphtha (petroleum), hydrodesulfurized heavy Flam. Liq. 3, H226; STOT RE 1, H372; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336	10-<25%
CAS: 64742-95-6 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336	5-<10%

- **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** Supply fresh air or oxygen; call for doctor.
- **After skin contact:**
Immediately rinse with water.
If skin irritation continues, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **4.2 Most important symptoms and effects, both acute and delayed**
Disorientation
Inhalation of concentrated vapours as well as oral intake will lead to anaesthesia-like conditions and headache, dizziness, etc.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters**
- **Protective equipment:** Mount respiratory protective device.

(Contd. on page 3)

-GB-

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.12.2021

Version number 10

Revision: 06.12.2021

Trade name: Foster 60-25

(Contd. of page 2)

- **Additional information** Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin, eyes and clothes.

- **6.2 Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

- **6.3 Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Use only in well ventilated areas.

- **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- **7.2 Conditions for safe storage, including any incompatibilities**

- **Storage:**

· **Requirements to be met by storerooms and receptacles:** No special requirements.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep container tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **8.1 Control parameters**

· **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

- **DNELs**

CAS: 64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

Oral	Long-term - systemic effects, general population	26 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, worker	44 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	26 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	330 mg/m ³ (Worker)
	Long-term - systemic effects, general population	71 mg/m ³ (General Population)

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.12.2021

Version number 10

Revision: 06.12.2021

Trade name: Foster 60-25

(Contd. of page 3)

CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	Long-term - systemic effects, general population	11 mg/kg bw/day (General Population)
Dermal	Long-term - systemic effects, worker	25 mg/kg bw/day (Worker)
	Long-term - systemic effects, general population	11 mg/kg bw/day (General population)
Inhalative	Long-term - systemic effects, worker	150 mg/m ³ (Worker)

· **Regulatory information**· **CAS No. Designation of material % Type Value Unit**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **Additional information:** The lists valid during the making were used as basis.

· **8.2 Exposure controls**· **Personal protective equipment:**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.



Filter A

· **Protection of hands:**

Not required.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber

Recommended thickness of the material: $\geq 0,12$ mm

· **Penetration time of glove material**

> 480 min.

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Use protective suit.

GB

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.12.2021

Version number 10

Revision: 06.12.2021

Trade name: Foster 60-25

(Contd. of page 4)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Appearance:

· Form:	Fluid
· Colour:	Black
· Odour:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Neutral

· Change in condition

· Melting point/freezing point:	Undetermined.
· Initial boiling point and boiling range:	155-194 °C

· Flash point: 43 °C (DIN 53213)

· Flammability (solid, gas): Not applicable.

· Ignition temperature: >200 °C

· Decomposition temperature: Not determined.

· Auto-ignition temperature: Product is not selfigniting.

· Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

· Lower:	0.7 Vol %
· Upper:	6 Vol %

· Vapour pressure At 20 °C: 3.7 hPa

· Vapour pressure At 50 °C: 15 hPa

· Density At 20 °C: 1.17 g/cm³ (DIN 51757)

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with water:

Not miscible or difficult to mix.

· Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

· Dynamic At 20 °C:	320,000 mPas
· Kinematic:	Not determined.

· Solvent content:

· Organic solvents: 17.6 %

· Solids content: 82.4 % (DIN 53216)

· 9.2 Other information

· VOC (EU):	17.63 %
· VOC (EU):	206.3 g/l
· VOCV:	17.63 %

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

· Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions No dangerous reactions known.

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.12.2021

Version number 10

Revision: 06.12.2021

Trade name: Foster 60-25

(Contd. of page 5)

- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** Carbon monoxide

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity** Based on available data, the classification criteria are not met.

- **LD/LC50 values relevant for classification:**

CAS: 64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

Oral	LD50	>15,000 mg/kg (RAT)
------	------	---------------------

Dermal	LD50	3,400 mg/kg (RABBIT)
--------	------	----------------------

CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.

Dermal	LD50	>2,000 mg/kg (RABBIT)
--------	------	-----------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation** Based on available data, the classification criteria are not met.
- **Serious eye damage/irritation** Based on available data, the classification criteria are not met.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Additional toxicological information:** No further relevant information available.
- **Ingestion:**
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure**
Causes damage to the central nervous system through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

- **12.1 Toxicity**

- **Aquatic toxicity:**

CAS: 64742-82-1 Naphtha (petroleum), hydrodesulfurized heavy

EC50/48 h	10-22 mg/l (DAPHNIA MAGNA)
-----------	----------------------------

EC50/72 h	4.6-10 mg/l (ALGAE)
-----------	---------------------

EC50/96 h	10-30 mg/L (Fish)
-----------	-------------------

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

- **Ecotoxicological effects:**

- **Remark:** Harmful to fish

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

- **12.5 Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.12.2021

Version number 10

Revision: 06.12.2021

Trade name: Foster 60-25


(Contd. of page 6)

· **12.6 Other adverse effects** No further relevant information available.

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Dispose of as dangerous waste.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|--|
| · 14.1 UN-Number | |
| · ADR/RID/ADN, IMDG, IATA | UN1133 |
| · 14.2 UN proper shipping name | |
| · ADR/RID/ADN | 1133 ADHESIVES |
| · IMDG, IATA | ADHESIVES |
| · 14.3 Transport hazard class(es) | |
| · ADR/RID/ADN, IMDG, IATA | |
| |  |
| · Class | 3 Flammable liquids. |
| · Label | 3 |
| · 14.4 Packing group | |
| · ADR/RID/ADN, IMDG, IATA | III |
| · 14.5 Environmental hazards: | |
| · Marine pollutant: | No |
| · 14.6 Special precautions for user | Warning: Flammable liquids. |
| · Hazard identification number (Kemler code): | 30 |
| · EMS Number: | F-E,S-D |
| · Stowage Category | A |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | Transport classification ADR/IMGD is based on packaging >30ltr(IMDG), <450ltr(ADR).
For other packaging units different classification can apply. |
| · ADR/RID/ADN | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |
| · Transport category | 3 |
| · Tunnel restriction code | D/E |

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.12.2021

Version number 10

Revision: 06.12.2021

Trade name: Foster 60-25

(Contd. of page 7)

· Remarks:	Transport is in line with the remarks under 2.2.3.1.5 of the ADR code till a volume of 450 ltr. If ADR > 450 ltr than class 3, packaging group III must be applied with accessory UN-number.
· IMDG	5L
· Limited quantities (LQ)	Code: E1
· Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Remarks:	Transport is in line with the remarks under 2.3.2.5 of the IMDG code till a volume of 30 ltr. If IMDG > 30 ltr than class 3, packaging group III must be applied.
· UN "Model Regulation":	UN 1133 ADHESIVES, 3, III

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labelling:**
Naphtha (petroleum), hydrodesulfurized heavy
- **Hazard statements**
H226 Flammable liquid and vapour.
H372 Causes damage to the central nervous system through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.
- **Precautionary statements**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243 Take action to prevent static discharges.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** *None of the ingredients is listed.*
- **Seveso category** *P5c FLAMMABLE LIQUIDS*
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** *5,000 t*
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** *50,000 t*

(Contd. on page 9)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 06.12.2021

Version number 10

Revision: 06.12.2021

Trade name: Foster 60-25

(Contd. of page 8)

· **National regulations:**· **Technical instructions (air):**

Class	Share in %
NK	17.6

· **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases***H226 Flammable liquid and vapour.**H304 May be fatal if swallowed and enters airways.**H335 May cause respiratory irritation.**H336 May cause drowsiness or dizziness.**H372 Causes damage to organs through prolonged or repeated exposure.**H411 Toxic to aquatic life with long lasting effects.*· **Department issuing SDS:** Product safety department.· **Contact:** temati@temati.com· **Abbreviations and acronyms:***RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)**IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)**ICAO: International Civil Aviation Organisation**ICAO-TI: Technical Instructions by the "International Civil Aviation Organisation" (ICAO)**ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**IATA: International Air Transport Association**GHS: Globally Harmonised System of Classification and Labelling of Chemicals**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**DNEL: Derived No-Effect Level (REACH)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Flam. Liq. 3: Flammable liquids – Category 3**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1**Asp. Tox. 1: Aspiration hazard – Category 1**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

GB